


**VENT Over Fascia Vent - G2500N**



- VENT Over Fascia Vent - G2500N**
- VENT Eaves Comb Filler - G1275**
- VENT Ventilation & Drainage Batten 20mm - VB20**
- VENT Ventilation & Drainage Batten 10mm - VB10**

**PROFILED STEEL ROOF CLADDING**  
 Ventilated Fascia - Skillion Roof with Eave  
 (25,000mm<sup>2</sup> tin/m)

A minimum of 20mm gap between the bottom purlin and Over Fascia Vent must be maintained to allow air flow into roof cavity

**Note 1**  
 Eave flashing required where all of the following conditions are met  
 - Roof pitch less than 10° and,  
 - Soffit width less than or equal to 100mm and,  
 - Wind zone is Very High or greater.

THIS IS A SUGGESTED METHOD OF VENTILATION BUT THE OVERALL DESIGN AND DIMENSIONS ARE THE RESPONSABILITY OF THE DESIGNER IN COMPLIANCE WITH THE NZ BUILDING CODE.

**Figure 16**  
**Steel Longrun Any Pitch - Skillion Roof With Eave**  
**Eave - G2500N + VB20 + VB10 + G1275**  
**Scale 1:5, 1:2**

**Contact:**  
 PH: 07 574 1116  
 EM: info@vent.nz

